

BEST AVAILABLE COPY

Neodymium

ARMSTRONG MAGNETICS INC

3411 James Street Road, #104, Bellingham, WA 98226, USA

www.armsmag.com



back home



[View cart](#)



[E-mail](#)

Toll Free: 1-800-965 4968 Tel: 360 647 8438 Fax: 360 539 1850 Web:

[Home](#)

[Permanent Magnets](#)

[Ceramic Magnets](#)

[Flexible Magnets](#)

[Magnetic Strips](#)

[Magnetic Sheets](#)

[Rare Earth Magnets](#)

[Neodymium](#)

[Samarium Cobalt](#)

[Bonded Neodymium](#)

[Magnetic Assembly](#)

[Cup assemblies](#)

[Neo assemblies](#)

[Channel Assembly](#)

[Magnetic Tools](#)

[Lift Magnets](#)

[Magnetic Pickup tools](#)

[FAQ on Ordering](#)

NEODYMIUM MAGNETS

Most powerful
easily corrupted
Hard and brittle

Stock sizes of Neodymium Magnets



Neodymium magnets are dark gray alloy. They are composed of Neodymium, Iron and Boron. Density of Neodymium magnets is .77Lb/in³ (7.5g/cm³).

Neodymium magnets are manufactured in a metallurgy process through alloying, crushing, powdering, pressing w/magnetic orientation, sintering, then cutting, coating, inspecting and packing before shipment.

Neodymium magnets offer the highest (BH)_{max} and high H_{ci}

(BH)_{max}, the Maximum Energy Product, of Neodymium magnets is highest of any kind of permanent magnets today in the world. (BH)_{max} at different grades of Neodymium magnets is 27 to 50 MGOe.

Neodymium magnets have extremely resistance to demagnetization with H_{ci}, Intrinsic coercive force, over 12,000 Oe.

Because of very high (BH)_{max} and H_{ci}, Neodymium magnets could be used as a reversible medium for large amount of energy transformation in miniaturized application where a strong magnetic demagnetization field exists, such as computer hard drive.

Armstrong Magnetics stocks N35 and N40 Neodymium magnets in disk and rectangle shapes for customers' immediate needs and accept special orders for custom Neodymium magnets.

Neodymium magnets are most powerful of any kind of magnetic materials

Br of Neodymium magnets are much more than 11,000 Gauss. Therefore, Neodymium magnets have strong holding strength on metal surface and could be used as component for holding, separating, etc.

<http://www.armsmag.com/neodymium.htm>

1/27/20

Neodymium magnets must be carefully handled to avoid personal injury and material damage due to its extremely magnetic strength and brittle property.

Neodymium magnets are sensitive to temperature change and even lose magnet properties at high temperature

Neodymium magnets lose -0.09 ~ -0.13% of Br/C and can work stably under 80°C for low Hci Neodymium magnets and 150°C for high Hci Neodymium magnets.

Neodymium magnets are corrupted in humid environment
Surface protection is strongly recommended, such as plating, varnishing and encapsulating.

Neodymium magnets are hard and brittle
Neodymium magnets can be abrasively machined with coolant served to absorb heating and dust. Without coolant, rare earth magnets can crack and chip by the heat produced during high speed cutting or grinding, and the sparks contain the easily oxidized grinding dust that can cause fire!

Tolerance of Neodymium magnets
Unless otherwise specified, tolerance on dimension of magnetization is $\pm 0.05\%$. Other dimensions are $\pm 1.5\%$ or $\pm 0.10\%$, whichever is greater.

MAGNETIC PROPERTY OF NEODYMIUM MAGNETS

Grade	Br (Gauss)	Hc (Oe)	Hci (Oe)	(BH)max (MGO)	Max Working Temp. (°C / °F)
35	11,700 - 12,100	>10,900	>12,000	35	80 / 176
40	12,500 - 12,800	>10,500	>12,000	40	80 / 176
35H	12,500 - 11,700	>11,000	>17,000	35	120 / 245
35SH	11,700 - 12,500	>11,000	>20,000	35	150 / 300



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☒ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.